

Tyre Size	Fitment	Tread Width (mm)	Overall Diameter (mm)	Measured Rim	Approved Rims	Tyre Pressure Guide		Tyre Warming
						Cold - Bar (PSI)	Hot Straight Out Of Warmers - Bar (PSI)	
K00 SLICK								
125/75 R16.5 NHS	Front	125	603	MT3.50	3.50 - 3.75	2.0 (29)	2.2 (32)	60 minutes @ 80 - 90°C
95/75 R17 NHS	Front	92	580	MT2.50	2.50 - 3.00	2.0 (29)	2.2 (32)	
120/70 R17 NHS	Front	116	600	MT3.50	3.50 - 3.75	2.1 (30)	2.3-2.4 (33-35)	
125/70 R17 NHS	Front	120	610	MT3.50	3.50 - 3.75	2.1 (30)	2.3-2.4 (33-35)	
115/75 R17 NHS	Rear	111	604	MT3.00	3.00 - 3.50	1.5 (22)	1.8 (26)	
160/60 R17 NHS	Rear	160	625	MT4.50	4.25 - 5.00	1.4 (20)	1.6-1.8 (23-26)	
180/60 R17 NHS	Rear	179	649	MT5.00	5.00 - 5.50	1.4 (20)	1.6-1.8 (23-26)	
190/60 R17 NHS	Rear	182	658	MT5.00	5.00 - 5.50	1.4 (20)	1.6-1.8 (23-26)	
200/60 R17 NHS	Rear	203	672	MT6.00	5.50 - 6.25	1.4 (20)	1.6-1.8 (23-26)	
200/65 R17 NHS	Rear	198	700	MT6.00	5.50 - 6.25	1.5 (22)	1.7-1.8 (25-26)	
K01 RAIN								
125/75 R16.5 NHS	Front	125	603	MT3.50	3.50 - 3.75	2.0 (29)	2.3 (33)	30 minutes @ 40°C
110/70 R17 NHS	Front	110	586	MT3.00	3.00 - 3.50	2.0 (29)	2.3 (33)	
125/70 R17 NHS	Front	122	600	MT3.50	3.50 - 3.75	2.0 (29)	2.3 (33)	
125/80 R17 NHS	Front	122	624	MT3.00	3.00 - 3.75	2.1-2.2 (30-32)	2.35 (34)	
140/70 R17 NHS	Rear	139	628	MT3.75	3.50 - 4.00	Heavy Rain 1.9 (28)	Heavy Rain 2.1 (30)	
						Wet Track 1.8 (26)	Wet Track 1.9 (28)	
160/60 R17 NHS	Rear	161	624	MT4.50	4.25 - 5.00	Heavy Rain 1.9 (28)	Heavy Rain 2.1 (30)	
						Wet Track 1.8 (26)	Wet Track 1.9 (28)	
190/55 R17 NHS	Rear	190	642	MT6.00	5.50 - 6.00	Heavy Rain 1.9 (28)	Heavy Rain 2.1 (30)	
						Wet Track 1.8 (26)	Wet Track 1.9 (28)	
K06 SUPERSPORT								
110/70 ZR17	Front			MT3.00	3.00 - 3.50	2.2 (32)	2.4 (35)	60 minutes @ 80 - 90°C
120/70 ZR17	Front			MT3.50	3.50 - 3.75	2.2 (32)	2.4 (35)	
140/70 ZR17	Rear			MT3.75	3.50 - 4.00	1.6-1.7 (23-25)	1.8-2.0 (26-29)	
150/60 ZR17	Rear			MT4.25	4.00 - 4.50	1.6-1.7 (23-25)	1.8-2.0 (26-29)	
160/60 ZR17	Rear			MT4.50	4.25 - 5.00	1.6 (23)	1.8 (26)	
180/55 ZR17	Rear			MT5.50	5.50 - 6.00	1.6 (23)	1.8 (26)	
180/60 ZR17	Rear			MT5.00	5.00 - 5.50	1.6 (23)	1.8 (26)	
190/55 ZR17	Rear			MT6.00	5.50 - 6.00	1.6 (23)	1.8 (26)	
200/55 ZR17	Rear			MT6.25	6.00 - 6.25	1.6 (23)	1.8 (26)	
K905 SPORT								
120/70 ZR17	Front			MT3.50	3.50 - 3.75	2.2 (32)	2.4 (35)	60 minutes @ 80 - 90°C
180/55 ZR17	Rear			MT5.50	5.50 - 6.00	1.6 (23)	1.8 (26)	
K97 CLASSIC RACING								
90/90 ZR18	Front			MT2.15	1.85 - 2.50	2.1 (30)	2.3 (33)	60 minutes @ 80 - 90°C
100/90 ZR18	Front			MT2.50	2.50 - 2.75	2.1 (30)	2.3 (33)	
110/80 ZR18	Front			MT2.50	2.50 - 3.00	2.1 (30)	2.3 (33)	
90/90 ZR18	Rear			MT2.15	1.85 - 2.50	1.5 (22)	1.7 (25)	
100/90 ZR18	Rear			MT2.50	2.50 - 2.75	1.5 (22)	1.7 (25)	
110/80 ZR18	Rear			MT2.50	2.50 - 3.00	1.5 (22)	1.7 (25)	
120/70 ZR18	Rear			MT3.50	3.50 - 3.75	1.5 (22)	1.7 (25)	
120/80 ZR18	Rear			MT3.50	2.50 - 3.00	1.5 (22)	1.7 (25)	
130/70 ZR18	Rear			MT3.50	3.50 - 4.00	1.5 (22)	1.7 (25)	

Please note that optimal hot pressures on track may vary depending on rider style, rider weight, track surface and temperature, and suspension set up. We recommend checking hot pressures in pit lane directly after a few laps and making small adjustments if necessary.

Tyre Size	Fitment			Measured Rim		Tyre Pressure Guide		Tyre Warming
K00 SLICK MINIBIKE								
100/85 R10 NHS	Front			MT2.50		1.3 (19)		70 - 90°C
100/90 R12 NHS	Front			MT2.50		1.3 (19)		
120/80 R10 NHS	Rear			MT2.75		1.1 (16)		
120/80 R12 NHS	Rear			MT2.75		1.1 (16)		

Please note that optimal hot pressures on track may vary depending on rider style, rider weight, track surface and temperature, and suspension set up. We recommend checking hot pressures in pit lane directly after a few laps and making small adjustments if necessary.

